

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

40.14 chs., and of the W. half mile is S.88\*51'W.,  
39.90 chs.

Land, mountainous.

Soil, clay loam, stony in places, first, second and third rate.

Timber, fir, cedar, pine.

Undergrowth, hazel, vine maple, fir, yew.

Retracement

Thence

North, retracing bet. secs. 26 and 27.

40.43 Fall 39 lks. W. of the 1/4 sec. cor.

80.89 Fall 44 lks. W. of the cor. of secs. 22, 23, 26, and 27.


The bearing and length of the S. half mile is N.0\*33'E.,  
40.43 chs., and of the N. half mile is N.0\*04'E.,  
40.46 chs.

Resurvey

The cor. of secs. 22, 23, 26, and 27 is located by reference to the original bearing trees.

At exact corner point

Set an iron post 3 ft. long, 2 ins. diam., 28 ins. in the ground for cor. of secs. 22, 23, 26 and 27 with brass cap marked



from which

A fir, 18 ins. diam., bears N.15'E., 44 lks. dist., marked T 30 S R 1 W S 23 B T: old B T.

A fir, 20 ins. diam., bears S.38'E., 23 lks. dist., marked T 30 S R 1 W S 26 B T: old B T.