

Retracement and Dependent Resurvey of Portion  
of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Resurvey

A fir, 20 ins. diam., bears S.43\*W., 42 lks. dist.,  
marked T 30 S R 1 W S 27 B T: old B T.

A fir, 48 ins. diam., bears N.35\*W., 13 lks. dist.,  
marked T 30 S R 1 W S 22 B T: old B T.

Thence

S.0\*04'W., on a true line, bet. secs. 26 and 27.

Over mountainous land, through heavy timber and dense  
undergrowth.

Asc. 730 ft. over NW. slope.

29.92 Top of ridge, bears E. and W.

Desc. 122 ft. over SW. slope.

35.78 Trail, bears NW. and SE.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in  
the ground for  $\frac{1}{4}$  sec. cor., for sec. 26 only, with  
brass cap marked

$\frac{1}{4}$ S26  
1923

from which

A fir, 7 ins. diam., bears N.9\*E., 32 lks. dist.,  
marked  $\frac{1}{4}$  S 26 B T.

A cedar, 18 ins. diam., bears S.85\*E., 45 lks.  
dist., marked  $\frac{1}{4}$  S 26 B T.

40.46 The  $\frac{1}{4}$  sec. cor. established for secs. 26 and 27 located  
by reference to the original bearing trees. I now  
change this corner to refer to sec. 27 only and

At exact corner point

Set an iron post 3 ft. long, 1 in. diam., 28 ins. in  
the ground for  $\frac{1}{4}$  sec. cor. of sec. 27 only, with  
brass cap marked

$\frac{1}{4}$ S27  
1923

from which