

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion
of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

An oak, 18 ins. diam., bears S.27*E., 168 lks.
dist., marked T 30 S R 1 E S 23 B T: old B T.
A pine, 26 ins. diam., bears S.23*W., 149 lks.
dist., marked T 30 S R 1 W S 22 B T: new B T.
An oak, 12 in. diam., bears N.75*W., 135 lks.
dist., marked T 30 S R 1 W S 15 B T: old B T.

The bearing and length of the S. half mile is N.0*18'E.,
40.68 chs., the S. half of the N. half mile is
N.2*19'W., 20.81 chs., and of the N. half of the N.
half mile is N.0*07'E., 20.07 chs.

Land, mountainous.

Soil, clay loam, second rate.

Timber, fir, pine, cedar, oak.

Undergrowth, willow, lilac, hazel and oak.

Thence

East, retracing bet. secs. 14 and 23.

Over mountainous land, through dead timber and dense
undergrowth.

Descend SE. slope, 200 ft.

- 0.09 Trail, bears NE. and SW.
2.80 Fence, bears NW. and SE.
6.00 Enter green timber.
9.35 Creek, 5 lks. wide, C. S. Asc. 505 ft. over W. slope
to $\frac{1}{4}$ sec. cor.
19.45 Trail, bears NW. and SE.
20.25 Fall 7 lks. S. of the 1/16 sec. cor. and cor. No. 2,
H E S No. 195, which is a granite stone, firmly set,
10x7x6 ins., above ground, marked 1/16 on N. and
2 H E S 195 on S. face; from which
A fir, 12 ins. diam., bears S.10*30'W., 88 lks.
dist., marked X 2 H E S 195 B T.