

## County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion  
of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

An oak, 6 ins. diam., bears N.9°E., 25 lks. dist.,

marked T 30 S R 1 W S 13 B T: new B T.

An oak, 5 ins. diam., bears S.20°E., 21 lks. dist.,

marked T 30 S R 1 W S 24 B T: old B T.

A fir, 14 ins. diam., bears S.65°W., 56 lks. dist.,

marked T 30 S R 1 W S 23 B T: new B T.

A fir, 12 ins. diam., bears N.71°W., 45 lks. dist.,

marked T 30 S R 1 W S 14 B T: new B T.

The bearing and length of the W. half of the W. half mile  
is N.89°48'E., 20.25 chs., of the E. half of the W.  
half mile is E. 20.32 chs., and of the E. half mile is  
N.89°14'E., 40.56 chs.

Land, mountainous.

Soil, stony clay loam, second and third rate.

Timber, fir, pine, oak, cedar.

Undergrowth, hazel, lilac, laurel.

Thence

North, retracing bet. secs. 13 and 14.

Over, mountainous land, through heavy timber and dense  
undergrowth.

Asc. 356 ft. over SW. slope.

2.87 Bluff, 20 ft. high, faces S.

11.00 Spur, slopes SE., desc. 65 ft. over NE. slope.

16.99 Creek, 4 lks. wide, C. SE. Asc. 456 ft. over SE. slope.

Enter old burn, bears NW. and SE.

40.33 Fall 9 lks. W. of the  $\frac{1}{4}$  sec. cor., located by reference  
to the original bearing trees, both dead, but in the  
position described in the field notes.

At exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the  
ground for  $\frac{1}{4}$  sec. cor., with brass cap marked