

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion
of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

Thence

S.89°56'E., retracing bet. secs. 12 and 13.

Over mountainous land, through dead timber and dense undergrowth in old burn.

Desc. 210 ft. over SE. slope.

7.94 Creek, 3 lks. wide, C. SE.

8.99 Creek, 5 lks. wide, C. SE.

12.41 Asc. 450 ft. over SW. slope.

15.30 Spring on line, flows SW.

39.68 Fall 19 lks. N. of the $\frac{1}{4}$ sec. cor. located by reference to the original SE. bearing tree, no other evidence found.

At exact corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
$$\begin{array}{c} S12 \\ \frac{1}{4} \\ S13 \\ 1923 \end{array}$$

from which

A pine, 36 ins. diam., bears S.28°E., 156 lks. dist., marked $\frac{1}{4}$ S 13 B T: old B T.A pine, 24 ins. diam., bears N.20°W., 133 lks. dist., marked $\frac{1}{4}$ S 12 B T: new B T.

Asc. 70 ft. on W. slope.

41.00 Fence, bears N. and S.

45.55 Top of ridge, bears NW. and SE. Leave burn, enter heavy timber, bears NW. and SE. Desc. 510 ft. over E. slope.

65.64 Spring on line, flows NE.

68.92 Creek, 1 lk. wide, C. NE.

69.96 Creek, 1 lk. wide, C. NE.

79.67 Fall 35 lks. S. of the point for the reestablished cor. of secs. 12 and 13, hereinafter described, originally