

County Surveyor's Record, Douglas County, Oregon

Retracement and Dependent Resurvey of Portion of Subdivisional Lines in T. 30 S., R. 1 W.

CHAINS

Retracement

Thence

South, retracing old E. bdy. of sec. 13.

Desc. 625 ft. over SE. slope.

5.51 Creek, 6 lks. wide, C. SE.

24.90 Same creek, 6 lks. wide, C. SW.

27.13 Same creek, 8 lks. wide, C. SE.

32.77 Right bank of S. fork of South Umpqua River, 50 lks. wide, C. W.

Asc. 210 ft. over N. slope.

40.27 Fall 121 lks. W. of the cor. established by Hathorn as the cor. of secs. 13, 18, 19 and 24, located by measurement from the original bearing trees which are in agreement with the field notes, except that the NE. tree bears N.31\*E., instead of N.47\*E., as reported. The SE. and NW. trees are dead.

At exact cor. point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for SE. cor. of original sec. 13, with brass cap marked

T30S  
R1W  
S13  
-----  
S24

from which

A fir, 16 ins. diam., bears S.1\*W., 35 lks. dist., marked T 30 S R 1 W S 24 A P B T: old B T.

A fir, 38 ins. diam., bears N.6\*W., 62 lks. dist., marked T 30 S R 1 W S 13 B T: new B T.

I obliterate marks on former bearing tree intended in the original survey to refer to sec. 18, T. 30 S., R. 1 E.

The bearing and length of this half mile is S.1\*43'E., 40.29 chs.