

Subdivision of T. 30 S., R. 1 W.

CHAINS

From the cor. of secs. 23 and 26 only.

N.0°20'E., on a random line on E. bdy. of sec. 23.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

82.53 Intersect E. and W. line, 3 lks. E. of the cor. of secs. 13, 14, 23 and 24, hereinbefore described.

Thence

S.0°19'W., on a true line, on E. bdy. of sec. 23.

Over mountainous land, through heavy timber and dense undergrowth.

Desc. 340 ft. over SW. slope.

11.30 Right bank of South Fork of South Umpqua River, C. W.

11.95 Left bank of same; asc. 800 ft. over NW. slope, through old burn.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ cor. of sec. 23 only, with brass cap marked

$\frac{1}{4}$ S23|
1923|

from which

A cedar, 24 ins. diam., bears S.1°W., 232 lks. dist., marked $\frac{1}{4}$ S23 B T.

No other trees in limits: raise mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Note: This cor. is established at 40 chs. from the N. treating sec. 23 as partially surveyed, in compliance with instructions referring to H. E. S. No. 195.

43.43 (40.00 chs. northing from cor. of secs. 24 and 25 only)

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for $\frac{1}{4}$ sec. cor. of sec. 24 only, with brass cap marked

| $\frac{1}{4}$ S24
|1923

from which

A fir, 16 ins. diam., bears N.45°E., 73 lks. dist., marked $\frac{1}{4}$ S 24 B T.