

## Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

- 40.00 The original  $\frac{1}{2}$  sec. cor., which is a basalt stone, 12x6x5 ins. above ground, firmly set marked  $\frac{1}{2}$  on W. face, hereafter this cor. will refer to sec. 36 only. I mark the  $\frac{1}{2}$  cor. stone S 36 on W. face, from which
- A fir, 30 ins. diam., bears N.29\*E., 22 lks. dist., I destroy marks on this tree.
- A fir, 20 ins. diam., bears S.75\*W., 14 lks. dist., marked  $\frac{1}{2}$  S 36 B T., old B T.
- A fir, 36 ins. diam., bears N.23\*W., 26 lks. dist., marked  $\frac{1}{2}$  S 36 B T., new B T.
- 43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 30 and 31, T. 30 S., R. 1 E., only, with brass cap marked
- |      |      |
|------|------|
| T30S | T30S |
| R1W  | S30  |
| S36  | S31  |
|      | R1E  |
|      | 1923 |
- from which
- A fir, 34 ins. diam., bears N.44\*E., 25 lks. dist., marked T 30 S R 1 E S 30 B T.
- A fir, 18 ins. diam., bears S.20\*E., 13 lks. dist., marked T 30 S R 1 E S 31 B T.
- 80.00 The cor. of secs. 25 and 36, which is a basalt stone 10x8x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general. I mark the cor. stone additionally S 36 on SW., and S 25 on NW. face.

- 3.58 North, resurveying the E. bdy. of sec. 25, T. 30 S., R. 1 W. Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{2}$  sec. cor., sec. 30 only, with brass cap marked

	$\frac{1}{2}$ S30
	1923

from which