

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

A fir, 28 ins. diam., bears N.26*E., 19 lks. dist.,
marked $\frac{1}{4}$ S 30 B T.

A fir, 12 ins. diam., bears S.53*E., 27 lks. dist.,
marked $\frac{1}{4}$ S 30 B T.

40.00 The original $\frac{1}{4}$ sec. cor., which is a basalt stone, 12x10x5
ins. above ground, firmly set, marked $\frac{1}{4}$ on W. face.
Hereafter this cor. will refer to sec. 25 only. I
mark the cor. stone $\frac{1}{4}$ S 25 on W. face, from which

A fir, 30 ins. diam., bears S.17*W., 35 lks. dist.,
marked $\frac{1}{4}$ S 25 B T., new B T.

A fir, 34 ins. diam., bears N.80*W., 33 lks. dist.,
marked $\frac{1}{4}$ S 25 B T., old B T.

I destroy the marks on the old B T in sec. 30.

43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in
the ground, for the cor. of secs. 19 and 30 only, with
brass cap marked

T30S	T30S
R1W	S19
S25	S30
	R1E
	1923

from which

A madrona, 16 ins. diam., bears N.20*E., 15 lks.
dist., marked T 30 S R 1 E S 19 B T.

A fir, 14 ins. diam., bears S.68*E., 37 lks. dist.,
marked T 30 S R 1 E S 30 B T.

80.00 The cor. of secs. 24 and 25, which is a basalt stone
10x6x5 ins. above ground, firmly set, marked and witnessed
as described by the surveyor general.

I mark the cor. stone S 25 on SW., and S 24 on NW. face.

North, resurveying the E. bdy., sec. 24, T. 30 S., R. 1 W.

3.58 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the