

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

ground, for $\frac{1}{4}$ sec. cor. of sec. 19 only, with brass cap marked

$\frac{1}{4}$ S19
1923

from which

A fir, 50 ins. diam., bears N.2*E., 356 lks. dist., marked $\frac{1}{4}$ S 19 B T.

A madrona, 6 ins. diam., bears S.5*E., 233 lks. dist., marked $\frac{1}{4}$ S 19 B T.

40.00 The original $\frac{1}{4}$ sec. cor., which is a basalt stone, 12x5x5 ins. above ground, firmly set, marked $\frac{1}{4}$ on W. face. Hereafter this cor. will refer to sec. 24 only.

I mark the cor. stone $\frac{1}{4}$ S 24 on W. face; from which

A fir, 30 ins. diam., bears S.75*W., 3 lks. dist., marked $\frac{1}{4}$ S 24 B T., old B T.

A fir, 30 ins. diam., bears N.58*W., 51 lks. dist., marked $\frac{1}{4}$ S 24 B T., new B T.

I obliterate the marks on the old B T in sec. 19.

43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 18 and 19 only, with brass cap marked

T30S | T30S
R1W | S18
S24 | S19
R1E
1923

from which

A fir, 22 ins. diam., bears N.2*E., 62 lks. dist., marked T 30 S R 1 E S 18 B T.

A fir, 17 ins. diam., bears S.66*E., 18 lks. dist., marked T 30 S R 1 E S 19 B T.

80.00 The cor. of secs. 13 and 24 only, which is a basalt stone, 8x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

I mark the cor. stone S 24 on SW., and S 13 on NW. face.