

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

80.00 The cor. of secs. 12 and 13 only, which is a basalt stone 15x6x5 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.  
I mark the cor. stone S 13 on SW., and S 12 on NW. face.

North, resurveying the E. bdy., of sec. 12, T. 30 S., R. 1 W.

3.58 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 7 only, with brass cap marked

|  $\frac{1}{4}$ S7  
1923

from which

A pine, 28 ins. diam., bears N.61\*E., 74 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

A pine, 28 ins. diam., bears S.11\*E., 41 lks. dist., marked  $\frac{1}{4}$  S 7 B T.

39.82 The original  $\frac{1}{4}$  sec. cor., which is a basalt stone, 12x5x5 ins. above ground, firmly set, marked  $\frac{1}{4}$  on W. face.

Hereafter this cor. will refer to sec. 12 only. I mark the cor. stone  $\frac{1}{4}$  S 12 on W. face; from which

A fir, 12 ins. diam., bears S.80\*W., 56 lks. dist., marked  $\frac{1}{4}$  S 12 B T., old B T.

A fir, 26 ins. diam., bears N.42\*W., 57 lks. dist., marked  $\frac{1}{4}$  S 12 B T., new B T.

I obliterate the marks on old B T in sec. 7.

43.58 Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for cor. of secs. 6 and 7 only, with brass cap marked

T30S | T30S  
R1W | S6  
S13 | S7  
R1E  
1923