

Dependent Resurvey of Willamette Meridian through T. 30 S.

CHAINS

from which

A fir, 22 ins. diam., bears N.67\*E., 85 lks. dist.,  
marked T-30 S R 1 E S 6 B.T.

A fir, 48 ins. diam., bears S.75\*E., 21 lks. dist.,  
marked T 30 S R 1 E S 7 B T.

79.82 The cor. of secs. 1 and 12 only, which is a basalt stone,  
12x8x5 ins. above ground, firmly set, marked and  
witnessed as described by the surveyor general. Both  
old bearing trees are dead.

I mark the stone S 12 on SW., and S 1 on NW. face; from  
which

A fir, 8 ins. diam., bears S.18\*W., 49 lks. dist.,  
marked T 30 S R 1 W S 12 B T., new B T.

A cedar, 24 ins. diam., bears N.31\*W., 129 lks.  
dist., marked T 30 S R 1 W S 1 B T., new B T.

North, resurveying the E. bdy. of sec. 1, T. 30 S., R. 1 W.

3.76 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
ground, for  $\frac{1}{4}$  sec. cor. of sec. 6 only, with brass cap  
marked

|  $\frac{1}{4}$ S6  
1923

from which

A fir, 10 ins. diam., bears N.71\*E., 17 lks. dist.,  
marked  $\frac{1}{4}$  S 6 B T.

A hemlock, 10 ins. diam., bears S.30\*E., 5 lks.  
dist., marked  $\frac{1}{4}$  S 6 B T.

40.23 The original  $\frac{1}{4}$  sec. cor., changed by Deputy Mensch under  
contract No. 797 to refer sec. 1 only, which is a  
basalt stone 12x6x5 ins. above ground, firmly set,  
marked and witnessed as described by the surveyor  
general.