

County Surveyor's Record, Douglas County, Oregon

Exterior Boundaries T.30 S., R.3 W.

CHAINS

80.00

Set a stone 16x12x12 ins., 12 ins. in the ground for cor. to secs. 1, 6, 7 and 12, marked with 1 notch on N and 5 notches on S edges; from which,

A Fir, 30 ins. diam., bears N.44*E., 97 lks. dist. marked T 30 S, R 2 W, S 6 B T.

A Fir, 24 ins. diam., bears S.45*E, 20 lks. dist. marked T 30 S, R 2 W, S 7 B T.

A Fir, 12 ins. diam., bears S.33*W, 60 lks. dist. marked T 30 S, R 3 W, S 12 B T.

A Fir, 33 ins. diam., bears N.67 $\frac{1}{2}$ *W, 19 $\frac{1}{2}$ lks. dist. marked T 30 S, R 3 W, S 1 B T.

Soil, third rate.

Land, Mountainous, 80.00 chs.

Heavily timbered with Fir, Laurel, Cedar, Chincapin and Maple, 80.00 chs.

Dense undergrowth of Vine-Maple, Laurel, Chincapin and Hazel, Willow, Balm, Huckleberry and Cedar, 80.00 chs.

see Pg 6918 for continuation of Bushney's survey notes.

Retracement of East Bdy. of T. 30 S., R. 3 W.,
As surveyed by Fred Mensch, Deputy Surveyor.
Under Contract No. 782, dated December 1, 1908

40.35

August 30 at 8 A.M. l.m.t. I set off 42*56' in the lat. arc. ^{409'} 907' N. on the decl. arc. and determine a meridian with the solar at the cor. of secs. 19, 24 25 and 30, on the W. bdy. of the tp.

Thence I retrace, North on E. bdy. sec. 24, T 30 S, R 3 W.

The $\frac{1}{4}$ sec. cor. which is a Cedar post, 4 ins. sq., 12 in. above ground, marked and witnessed as described by the surveyor general, the course of this line is North and the distance is 40.35 chs.

Commencing at the $\frac{1}{4}$ sec. cor. I retrace North on E. bdy. sec. 24, T 30 S, R 3 W.