

## Retracement of East Bdy., T. 30 S., R 3 W.

CHAINS

From the cor. of Tp. 30 S, R's 2 and 3 W., I retrace  
East on N. bdy. sec. 1, T 31 S, R 3 W.

33.35

The NE cor. of T 31 S., R 3W, which is a granite stone  
5x10x8 ins above ground, firmly set, marked and  
witnessed as described by the surveyor general bears  
N 33 lks. dist.

The course of this line is N.89°26'E., and the distance  
is 33.35 chs.

September 6: At this cor. I set off 6°29'N., on the  
decl. arc. and at 11 H. 58 m. a. m. 1. m. t. observe  
the sun on the meridian. the resulting lat. is  
42°54'

---

Re-survey of West Bdy., of T 30 S., R 2 W.  
Same Deputy and Contract

---

I return to the cor. of Tp. 30 S. R'S 2 and 3 W. thence  
I run N.0°39'W., on W. bdy. sec.. 31

Over mountainous land, heavily timbered and covered  
with dense undergrowth.

Asc. S slope.

1.75

Ridge point descending W. Desc. NW. slope.

9.25

Ravine, Course W. Asc., SW. slope.

23.25

Ridge, bears E and W. Desc. NW. slope.

31.04

A maple, 4 in. diam., for  $\frac{1}{4}$  sec. cor. on W. bdy. sec.

31, I mark  $\frac{1}{4}$  S 31 on E side, from which,

A Maple, 6 in. diam., bears N.12°E., 35 lks. dist.

marked  $\frac{1}{4}$  S 31 B T.

A Maple, 6 in. diam., bears S.76°E., 8 lks. dist.

marked  $\frac{1}{4}$  S 31 B T.

31.44

Ravine, course W. Ascend S. slope.

31.54

I re-establish the old  $\frac{1}{4}$  sec. cor. in its original  
position as the  $\frac{1}{4}$  sec. cor. on E bdy. sec. 36,  
T 30 S, R 3 W, as follows.

Set a slate stone 12x8x6 ins. 8 ins. in the ground for  
 $\frac{1}{4}$  sec. cor. on E. bdy. sec. 36, marked  $\frac{1}{4}$  on W face,  
from which,