

County Surveyor's Record, Douglas County, Oregon

Re-survey of Subdivision Lines of T. 30 S., R. 2 W.
Same Deputy and Contract.

CHAINS	
	At the cor. of secs. 7, 12, 13, and 18 on the E. bdy. of the Tp.
	Thence I run,
	S.89°58'W., on S bdy. sec. 12.
	Over mountainous land, heavily timbered and covered with dense undergrowth.
	Ascend E. slope.
3.80	Trail bears N and S.
26.00	Ridge bears SE. and W, thence along ridge.
35.00	Leave ridge, bears NW.
	Along S. slope.
40.00	Set a porphyry stone 12x8x6 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor. on S bdy. sec. 12, marked $\frac{1}{4}$ on N face, from which,
	A Fir, 18 ins. diam., bears N.40°E., 9 lks. dist. marked $\frac{1}{4}$ S 12 B T.
	A Fir, 18 ins. diam., bears N.70 $\frac{1}{2}$ °W., 46 lks. dist. marked $\frac{1}{4}$ S 12 B T.
40.88	I re-establish the old $\frac{1}{4}$ sec. cor. in its original position as the $\frac{1}{4}$ sec. cor. on N bdy. sec. 13, only as follows,
	Set a porphyry stone 12x9x8 ins., 8 ins. in the ground for $\frac{1}{4}$ sec. cor. on N bdy. sec. 13, marked $\frac{1}{4}$ on S face, from which,
	A Fir, 18 ins. diam., bears S.77°E., 51 lks. dist. marked $\frac{1}{4}$ S 13 B T.
	A Fir, 18 ins. diam., bears S.70°W., 17 lks. dist. marked $\frac{1}{4}$ S 13 B T.
	Obliterate marks on former bearing tree referring to sec. 12.
	Thence N. 89°49'W.
60.00	Ridge bears NE and SW.
80.00	Set a porphyry stone 12x8x6 ins. 8 ins. in the ground, for cor. of secs. 11 and 12, marked with 1 notch on E edge, from which,
	A Madrone, 18 ins. diam., bears N.41 $\frac{1}{2}$ °E., 42 lks. dist. marked T 30 S, R 2 W, S 12 B T.