

Retracement of Subdivision Lines of T. 30 S., R 2 W.

CHAINS

A Fir, 10 ins. diam., bears N.30*W., 15 lks. dist.
marked $\frac{1}{4}$ S. 19 B T.

Descend steep E slope to Coffee Creek.

56.25 Coffee Creek, 20 lks. wide, course S.

Ascend W slope.

75.00 Ridge point descending SW.

Along S. slope

80.85 The cor. of secs. 29 and 30

Thence N.89*49'E.

81.43 The closing cor. of secs. 19 and 20.

Land, mountainous.

Soil, clay and stony, second and third rate.

Timber, Fir, Oak, Madrone.

Undergrowth, Oak, Hazel, Fir, Vine-maple.

Mountainous or heavily timbered land or land covered
with dense undergrowth and exceptionally difficult
to survey, 81.43 chs.

Re-survey of Subdivision Lines of T. 30 S., R.2 W.
Same Deputy and Contract.

N.89*48'E., on S bdy. sec. 20.

Over mountainous land, heavily timbered and covered
with dense undergrowth.

Along S. slope.

17.40 Creek, 5 lks. wide, course SW.

Gradually ascend NW, slope.

39.79 The old $\frac{1}{4}$ sec. cor.

I re-establish this corner in its original position as
the $\frac{1}{4}$ sec. cor. on N.bdy. sec. 29, only, as follows;

Set a slate stone 15x8x5 ins., 10 ins. in the
ground for $\frac{1}{4}$ sec. cor. on N bdy. sec 29, marked
 $\frac{1}{4}$ on S face, from which,

A Madrone, 5 ins. diam., bears S.10*E., 8 lks.
dist. marked $\frac{1}{4}$ S 29 B T.

A Madrone, 24 ins. diam., bears S.40*W., 9 lks.
dist. marked $\frac{1}{4}$ S 29 BT.