

North Boundary of T. 30 S., R.2 W.

CHAINS

- 16.75 Ravine, course S.
- 20.25 Ridge point descending S.
- 22.25 Ravine, course S.
- 32.00 Ridge point descending S.
- 36.50 Ravine, course S.
- 40.00 Set a porphyry stone 14x12x6 ins., 9½ ins. in the ground, for ¼ sec. cor. marked ¼ on N. face, from which,
 - A Fir, 10 ins. diam., bears N.35*W., 4 lks. dist. marked ¼ S 31 B T.
 - A Madrone, 6 ins. diam., bears ^{1/85}S.40°E ^{v.r.}, 3½ lks. dist. marked ¼ S 6 B T.
- 43.75 Trail on summit of high ridge bears N and S, Descend steep W. slope.
- 67.25 Coffee Creek, 20 lks. wide, course S. Ascend E. slope.
- 85.50 Creek, 1 lk. wide, course SE.
- 85.75 Interest E. bdy. T 29 S., R 3 W, 6.16 chs. S. of ¼ sec. cor. on E. bdy. sec. 36.

Set a slate stone 18x10x10 ins. 12 ins. in the ground, for closing cor. of Tps 29 and 30 S, R 2 W. marked C C on E, with 6 grooves on NS. and E. faces, from which,

 - A Hemlock 12 ins. diam., bears N.44*E., 22lks. dist. marked T 29 S, R 2 W, S 31 B T.
 - A Hemlock, 10 ins. diam. bears S.40½*E, 48 lks. dist. marked T 30 S, R 2 W, S 6 B T.

The old ¼ sec. cor. in E. bdy. sec. 36 is nearly obliterated. No trace remains of the post and the marks on the bearing trees are defaced.

I re-establish the cor. in its original position as the ¼ sec. cor. on E. bdy. sec. 36 T 29 S, R 3 W, only as follows:

Set a slate stone 18x15x10 ins. 10 ins. in the ground,