

## County Surveyor's Record, Douglas County, Oregon

## Subdivision Lines of T. 30 S., R. 2 W.

CHAINS

from which,

A Fir, 48 ins. diam., bears N.60\*E., 26 lks. dist.  
marked, T. 30 S, R 2 W, S 10 B T.

Gradually ascend E. slope.

1.75 Set temp. cor. for secs. 15 and 16. As the line between these secs. will be extended North from the  $\frac{1}{4}$  sec. cor. I do not set permanent cor. at this time.

19.50 Ridge, bears NE and SW.

22.00 A spring, flows NE.

29.00 A spring flows NE.

40.00 Set a basalt stone 16x10x6 ins. 11 ins. in the ground for  $\frac{1}{4}$  sec. cor. on S' bdy. sec. 9 marked  $\frac{1}{4}$  on N. face from which,

A Fir, 15 ins. diam., bears N.32\*E., 34 lks. dist. marked  $\frac{1}{4}$  S 9 B T.

A Fir, 24 ins. diam., bears N.84\*W., 82 lks. dist. marked  $\frac{1}{4}$  S 9 B T.

41.75 Set temporary  $\frac{1}{4}$  sec. cor. on N. bdy., sec. 16.

52.00 Divide between S. Umpqua River and Coffee Creek, bears N and S.

56.00 Trail bears NW. and SE.

64.15 Trail to Tiller and wagon road survey bears N and S.

67.80 Trail to Ferdue bears NE and SW.

Descend W. slope.