

## Subdivision Lines of T. 30 S., R. 2 W.

## CHAINS

- Descend NW. slope.
- 4.00 Ravine, course NW.
- 11.50 Creek, 2 lks. wide, course NW.
- 18.00 Creek, 1 lk. wide, course NE.
- Ascend E. slope.
- 24.25 Ridge point descending N.  
descend NW. slope.
- 35.75 Creek, 1 lk. wide, course N.
- 38.25 Creek, 1 lk. wide, course NE.
- Ascend E. slope.
- 40.00 Set a slate stone 12x8x6 ins. 8 ins. in the ground for  $\frac{1}{4}$  sec. cor. on S. bdy. sec 8. marked  $\frac{1}{4}$  on N face from which,
- A Maple, 12 ins. diam., bears N.40\*E., 44 lks. dist. marked  $\frac{1}{4}$  S.S.B T.
- A Fir 24 ins. in diam. bears N 41 $\frac{1}{2}$ \* W 33 lks. dist. marked  $\frac{1}{4}$  S S B T.
- 41.75 Set a slate stone 12x7x7 ins. 8 ins. in the ground for  $\frac{1}{4}$  sec. cor. on N bdy. sec. 17 marked  $\frac{1}{4}$  on S face from which
- A Cedar 18 ins. diam. bears S.49 $\frac{1}{2}$ \*E., 36 lks. dist. marked  $\frac{1}{4}$  S 17 B T.
- A Fir, 40 ins. diam., bears S.67\*W., 30 lks. dist. marked  $\frac{1}{4}$  S 17 B T.
- 51.50 Ridge point descending NW.  
Descend gradually along N. slope.
- 54.00 Creek 1 lk. wide course N.
- 60.00 Ridge point descending NW.
- 80.00 Set a slate stone 16x16x4 ins. 11 ins. in the ground for cor. of secs. 7 and 8, marked with 5 notches on E edge from which,
- A Fir, 16 ins. diam. bears N.53\*E., 60 lks. dist. marked T 30 S, R 2 W, S-8 B T.
- A Fir, 4 ins. diam. bears N.16 $\frac{1}{2}$ \*W., 34 lks. dist. marked T 30 S, R 2 W, S 7 B T.