

## Subdivision Lines of T. 30 S., R. 2 W.

## CHAINS

A Hemlock 5 ins. diam. bears S.21\*E., 60 lks. dist.  
marked  $\frac{1}{4}$  S 18 B T.

A Fir 18 ins. diam. bears S.20\*W., 39 lks. dist.  
marked  $\frac{1}{4}$  S 18 B T.

47.25 Granite Creek, 8 lks. wide, course S.  
Over creek bottom.

52.25 Trail bears N. and S.

53.00 Enter old placer excavation.

54.75 Coffee Creek, 10 lks. wide, course S. Leave placer  
excavation.

Asc. E. slope.

63.50 Creek, 3 lks. wide, course SE.

75.00 Ridge bears NW. and SE.

Along S. slope.

82.90 Intersect W. bdy. of the Tp., 71 lks. N. of the cor.  
of secs. 7, 12, 13 and 18, which is a decayed post,  
marked and witnessed as described by the surveyor  
general.

Set a granite stone 20x12x6 ins., 15 ins. in the  
ground for closing cor. of secs. 7 and 18, marked  
CC on E. with 2 grooves on N. and 4 grooves on S.  
face, from which,

A Fir, 20 ins. diam. bears N.88\*E., 104 lks. dist.  
marked T 30 S R 2 W S 7 B T.

A Fir, 12 ins. diam. bears S.52\*E., 14 lks. dist.  
marked T 30 S R 2 W S 18 B T.

I re-establish the old cor. of secs 7, 12, 13 and 18,  
in its original position as the cor. of secs. 12 and  
13, T 30 S R 3 W only, as follows:

No stones available. Set a Fir post 3 ft. long, 4 ins.  
sq., 24 ins. in the ground for cor. of secs. 12 and  
13, marked T 30 S S 13 on SW. and R 3 W S 12 on NW.  
side, with 2 notches on N. and 4 notches on S. edges,  
from which,

A Cedar, 18 ins. diam. bears S.33\*W., 16 lks. dist.  
marked T 30 S R 3 W S 13 B T.