

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 30 S., R. 2 W.

CHAINS	to survey, 80.00 chs.
	August 26, 1909.
	August 27: I commence at the $\frac{1}{4}$ sec. cor. bet. secs. 16 and 21.
	Thence I run
	W. on a random line bet. secs. 16 and 21.
22.90	No trace of witness cor. is found after careful search
39.17	Intersect E. bdy. sec. 20, 150 lks. S.0*2'W. (see. line bet. secs. 20 and 21) of the cor. of secs. 17 and 20.
	Set a granite stone 16x10x8 ins., 11 ins. in the ground, for closing cor. of secs. 16 and 21, marked C C on E. with 3 grooves on N. and S. faces, from which,
	A Fir, 30 ins. diam., bears N.25*E., 38 lks. dist. marked T 30 S R 2 W S 16 B T.
	A Fir, 24 ins. diam., bears S.72*E., 19 lks. dist. marked T 30 S R 2 W S 21 B T.
	Thence I run
	E. on true line bet. secs. 16 and 21.
	Over mountainous land, heavily timbered and covered with dense undergrowth.
	Desc. E. slope.
16.10	Creek, 3 lks. wide, course S.
16.60	Ridge point descending S.
19.40	Salt Creek, 5 lks. wide, course S.
20.65	Trail to Tiller and wagon road survey.
	Enter A. J. Potier's clearing.
33.20	Enter swamp.
35.75	Leave swamp.
	Asc. W. slope.
36.75	Leave clearing.
37.75	Fence bears N. and S.
39.17	The $\frac{1}{4}$ sec. cor.