

## Subdivision of T. 30 S. R. 2 W.

CHAINS	
	<p>Sq., 12 ins. above ground, marked and witnessed as described by the surveyor general.</p> <p>Set a Cedar post ( No stones available) 3 ft. long 4 ins. sq., 24 ins. in the ground, for closing cor. of secs. 18 and 19, marked C C T 30 S R 2 W on E. , S 18 on N. and S 19 on S. face, with 3 grooves on N. and S. faces, from which,</p> <p>A Fir, 15 ins. diam., bears N.78<math>\frac{1}{2}</math>*E., 29 lks. dist. marked T 30 S R 2 W S 18 B T.</p> <p>A Fir, 24 ins. diam., bears S.55<math>\frac{1}{2}</math>*E., 28 lks. dist. marked T 30 S R 2 W S 19 B T.</p> <p>I obliterate marks on former cor. and bearing trees referring to T 30 S R 2 W.</p> <p>From the closing cor. of secs. 18 and 19, I run East on a true line bet. secs. 18 and 19.</p> <p>Over mountainous land, heavily timbered and covered with dense undergrowth.</p> <p>Along ridge bears E. and W.</p>
15.90	<p>Wagon road. Coffee Creek to Perdue, bears N. and S. Along N. slope.</p>
21.50	<p>Head of ravine, course N.</p>
28.75	<p>A Spring, bears N., 10 lks. dist. Asc. W. slope.</p>
32.50	<p>Ridge bears N. and S. Desc. E. slope.</p>
41.47	<p>A Cedar, 48 ins. diam., for <math>\frac{1}{4}</math> sec. cor, I mark <math>\frac{1}{4}</math> S 18 on N. and 19 on S. side, from which,</p> <p>A Fir, 20 ins. diam., bears N.1*E., 30 lks. dist. marked <math>\frac{1}{4}</math> S 18 B T.</p> <p>A Fir, 24 ins. diam., bears S.62*E., 34 lks. dist. marked <math>\frac{1}{4}</math> S 19 B T.</p>
49.50	<p>Creek, 1 lk. wide, course NE.</p>
53.50	<p>Coffee Creek, 20 lks. wide, course S. Asc. steep W. slope.</p>