

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 30 S., R. 2 W;

CHAINS

- 53.80 Trail bears N. and S.
- 69.00 Top of steep ascent. End of ridge, bears E.
Thence along ridge.
- 81.47 The cor. of secs. 17, 18, 19 and 20.
Land, mountainous.
Soil, granite, 2nd and 3rd rate.
Timber, Fir, Hemlock, Cedar.
Undergrowth, Hazel, Lilac, Hemlock, Vine Maple.
Mountainous or heavily timbered land or land covered
with dense undergrowth and exceptionally difficult
to survey, 81.47 chs.
-
- 40.00 S.0*2'E. on a random line bet. secs. 19 and 20.
Set temp. $\frac{1}{4}$ sec. cor.
- 82.71 Intersect N. bdy. sec. 29., 58 lks. N.89*48'E. of
the cor. of secs. 19, 20, 29 and 30.
Set a quartz stone 15x8x6 ins., 10 ins. in the ground,
for closing cor. of secs. 19 and 20, marked C C on
N. with 5 grooves on E. face, from which,
A Fir, 10 ins. diam., bears N.7*E., 30 lks. dist.
marked T 30 S R 2 W S 20 B T.
A Fir, 12 ins. diam., bears N.50*W., 24 lks. dist.
marked T 30 S R 2 W S 19 B T.
I re-establish the old cor. of secs. 19, 20, 29 and 30
in its original position as the cor. of secs. 29 and
30 only, as follows:
Set a granite stone 14x10x7 ins., $9\frac{1}{8}$ ins. in the ground,
for cor. of secs. 29 and 30, marked with 2 notches
on S. and 5 notches on E. edge, from which,
A Fir, 16 ins. diam., bears S.58 $\frac{1}{2}$ *E., 34 lks. dist.
marked T 30 S R 2 W S 29 B T.
A Fir, 10 ins. diam., bears S.57 $\frac{1}{2}$ *W., 34 lks. dist.
marked T 30 S R 2 W S 30 B T.
From the closing cor. of secs. 19 and 20, I run
N.0*2'W. on true line bet. secs. 19 and 20.