

Subdivision of T. 30 S. R. 2 W.

CHAINS

40.00 Set temp. $\frac{1}{2}$ sec. cor.80.85 Intersect S. bdy. sec. 29, 88 lks. ^EW. of the cor. of
secs. 29, 30, 31 and 32.

Set a slate stone 18x10x5 ins., 12 ins. in the ground;
for closing cor. of secs. 31 and 32, marked C C on S.
with 1 groove on S. and 5 grooves on E. face, from
which,

A Live Oak, 12 ins. diam., bears S.24*E., 17 lks.
dist. marked T 30 S R 2 W S 32 B T.

A Fir, 12 ins. diam., bears S.64 $\frac{1}{2}$ *W., 50 lks. dist.
marked T 30 S R 2 W S 31 B T.

The old cor. of secs. 29, 30, 31 and 32 is nearly
obliterated, the SW. bearing tree being the only re-
maining evidence.

I re-establish the cor. in its original position as
the cor. of secs. 29 and 30 only, as follows:

Set a slate stone 18x12x6 ins., 12 ins. in the ground,
for cor. of secs. 29 and 30, marked with 5 notches
on E. edge, from which,

A Live Oak, 4 ins. diam., bears N.59 $\frac{1}{2}$ *E., 38 lks.
dist. marked T 30 S R 2 W S 29 B T.

A Fir, 20 ins. diam., bears N.75*W., 49 lks.
dist. marked T 30 S R 2 W S 30 B T.

Marks on old bearing tree referring to sec. 31 are
sufficiently obliterated.

From the closing cor. of secs. 31 and 32, I run
S.0*1'E. on a true line bet. secs. 31 and 32.

Over mountainous land, heavily timbered and covered
with dense undergrowth.

Desc. S. slope.

5.50 Wagon road bears E. and W.

7.00 S. Umpqua River, right bank, course W.

8.60 Leave River.

Asc. N. slope.