

Resurvey of Exteriors of T. 30 S., R. 4 W.

CHAINS		
		Va. 19*24'E
	Descend through Oak openings	
3.00	Gully, course W. Begin ascending.	-40
7.00	Top of W. end of spur, bears E. and W.	+60
10.00	Foot of descent. Begin ascent.	-30
18.00	Top of spur, bears E. and W.	+50
22.00	Leave Oak openings, enter prairie E. and W.	
29.50	Foot of hill, course E. and W.	-60
30.00	Enter field, Va. 18*12'E.	
38.00	Leave field, enter Oak underbrush.	
39.00	The $\frac{1}{2}$ sec. cor post is gone, but both bearing trees are standing. I restore this cor. by setting a W. Oak post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S. on W. face, from which	+15
	A B. Oak, 14 ins. diam., bears S.80*W., 50 lks. dist., marked $\frac{1}{4}$ S B T.	
	A B. Oak, 16 ins. diam., bears S.62*E., 135 lks. dist., marked $\frac{1}{4}$ S B T.	
	These are the old bearing trees whose marks I renew.	
	Thence	
	S.1*1'W., on true line between secs. 1 and 6.	
		Va. 18*40'E
	Ascend W. hill side. Oak openings.	
14.50	Top of ascent, begin descent of W. slope.	+75
26.00	Foot of hill, enter prairie, bears E. and W.	-85
32.50	Level bottom.	-20
37.40	County road to Canyonville, course W. Enter Ash, Maple, and Fir timber.	
39.15	The cor. to secs. 1, 12, 6 and 7.	
	Land, hilly.	
	Soil, gravelly loam, 2nd rate.	