

County Surveyor's Record, Douglas County, Oregon

6937

Subdivisions of T. 30 S., R. 3 W.

CHAINS		
.35	A stream, 2 lks. wide, course SE. Ascend.	+500
1.45	A Fir, 36 ins. diam., on line marked with 2 notches on N. and S. sides.	
5.35	A stream, 1 lk. wide, course S.15*W.	
16.00	Same stream, course S.15*E.	
18.35	A Fir, 15 ins. diam., on line marked with 2 notches on N. and S. sides.	
35.00	Top of ridge and descend.	-300
40.00	Set a Fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S. on W. face, from which A Fir, 26 ins. diam., bears N.47 $\frac{1}{2}$ *W., 19 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 10 ins. diam., bears N.21 $\frac{1}{2}$ *E., 67 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S B T.	
40.50	A Fir, 26 ins. diam., on line marked with 2 notches on N. and S. sides.	
43.25	A ravine, course E. and W. Ascend.	+200
61.50	A Fir, 16 ins. diam., on line marked with 2 notches on N. and S. sides.	
70.75	Top of ridge, course NE. and SW. Descend.	-175
80.00	Set a stone, 13 x 8 x 5 ins. 9 ins. in the ground, for cor. to secs. 2, 3, 10 and 11, marked with 2 notches on E. and 5 notches on S. edges, from which A Laurel, 10 ins. diam., bears N.65*E., 33 lks. dist., marked T 30 S R 3 W S 2 B T. A Fir, 8 ins. diam., bears S.58 $\frac{1}{2}$ *E., 28 lks. dist., marked T 30 S R 3 W S 11 B T.. A Laurel, 8 ins. diam., bears S.52*W., 38 $\frac{1}{2}$ lks. dist., marked T 30 S R 3 W S 10 B T. A Fir, 9 ins. diam., bears N.31 $\frac{3}{4}$ *W., 104 lks. dist., marked T 30 S R 3 W S 3 B T.	
	Land, mountainous. 80.00 chs.	
	Soil, 3rd rate.	
	Heavily timbered with Fir, Laurel, Cedar and Maple.	