

Subdivisions of T. 30 S., R. 3 W.

CHAINS		
	An Oak, 15 ins. diam., bears N.35*W., 38 lks. dist., marked T 30 S R 3 W S 21 B T.	
	The witness tree in sec. 27 is burnt. In it's stead I mark a Fir, 10 ins. diam., which bears S.60 $\frac{1}{2}$ *E., 98 $\frac{1}{2}$ lks. dist., marked T 30 S R 3 W S 27 B T.	
	Thence I run N.0*2'W., secs. 21 and 22.	
	Va. 18 3/4*E	
	Ascend in Fir, Laurel and Oak timber.	+50
10.50	Top of ridge, course NW. and SE. Descend.	-80
22.50	A dry ravine, course NW. and SE; Ascend.	+50
24.32	A Fir, 30 ins. diam., on line marked with 2 notches on N. and S. sides.	
24.75	Descend.	-200
36.60	A stream, 4 lks. wide, course SE. Ascend.	+400
40.00	Set a quartz stone, 12 x 12 x 6 ins. 8 ins. in the ground, for $\frac{1}{4}$ sec. cor. marked $\frac{1}{4}$ on W. face, from which	
	A Fir, 12 ins. diam., bears N.42 $\frac{1}{4}$ *E., 9 lks. dist., marked $\frac{1}{4}$ S B T.	
	A Fir, 15 ins. diam., bears S.17*W., 56 lks. dist., marked $\frac{1}{4}$ S B T.	
56.50	Top of mountain and descend.	-350
74.05	A Fir, 24 ins. diam., on line marked with 2 notches on N. and S. sides.	
80.00	Set a Chinquapin post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 15, 16, 21 and 22, marked T 30 S S 15 on NE R 3 W S 22 on SE S 21 on SW and S 16 on NW faces, with 3 notches on E. and S. edges, from which	
	A Fir, 16 ins. diam., bears N.75*E., 33 lks. dist., marked T 30 S R 3 W S 15 B T.	