

County Surveyor's Record, Douglas County, Oregon

6963  
91

Subdivisions of T. 30 S., R. 3 W.

CHAINS		
19.75	Ascend.	+500
35.00	Top of ridge, course NW. and SE. Descend.	-350
40.00	<p>Set a Fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for <math>\frac{1}{4}</math> sec. cor., marked <math>\frac{1}{4}</math> S. on W. face, from which</p> <p>A Cedar, 10 ins. diam., bears N.88<math>\frac{1}{2}</math>*W., 25 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p> <p>A Chinquapin, 6 ins. diam., bears N.78*E., 26 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p>	
48.00	A stream, 1 lk. wide, course SE. Ascend.	+40
50.75	Descend.	-30
51.51	A ravine, course E. and W. Ascend.	+250
52.05	A Fir, 36 ins. diam., on line marked with 2 notches on N. and S. sides.	
73.25	Top of ridge, course SW. and NE. Descend.	-200
74.90	A Fir, 36 ins. diam., on line marked with 2 notches on N. and S. sides.	
80.00	<p>Set a Fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. to secs. 8, 9, 16 and 17, marked T.30 S S 9 on NE R 3 W S 16 on SE S 17 on SW and S 8 on NW faces, with 4 notches on E. and S. edges, from which</p> <p>A Fir, 16 ins. diam., bears N.15<math>\frac{1}{2}</math>*E., 53 lks. dist., marked T.30 S R 3 W S 9 B.T.</p> <p>A Maple, 6 ins. diam., bears S.17 <math>\frac{3}{4}</math>*E., 26<math>\frac{1}{4}</math> lks. dist., marked T.30 S R 3 W S 16 B T.</p> <p>A Fir, 11 ins. diam., bears S.56<math>\frac{1}{4}</math>*W., 30 lks. dist., marked T 30 S R 3 W S 17 B T.</p> <p>A Fir, 22 ins. diam., bears N.13<math>\frac{1}{2}</math>*W., 49 lks. dist., marked T 30 S R 3 W S 8 B T.</p>	
	Land, mountainous. 80.00 chs.	
	Soil, 3rd rate.	