

County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 30 S., R. 4 W.

CHAINS
19.54

A Balm of Gilead, 18 ins. diam., on left bank. The bed of this river is composed of large rock which, when broken has a saline taste. About 15 or 20 chs. below the line on the right bank at the base of rocky bluff and water's edge, Melacite and Pyrites of Copper is found in small quantities among the rocks.

19.54 Enter beautiful prairie, course with river.

40.00 Set $\frac{1}{4}$ Sec. post. Deposited quart of stone and raised a mound with trench, as per instructions.

48.00 A trail, course E. and W.

Var. 16°35'E.

48.00 Trail, C. E. and W.

70.00 Leave prairie and enter Oak openings, course NW. and E.

80.00 Set post Cor. Secs. 13, 18, 19 and 24; from which

A B. Oak, 18 ins. diam., bears S.68°W., 131 lks. dist.,

A B. Oak, 16 ins. diam., bears N.20°E., 200 lks. dist.

Made trench as per instructions.

South of river, level prairie, 1st rate. North of river hilly, 3d rate. Oak openings.

Aug. 11, 1851.

Var. 16°E.

South, on the W. Bdy. of Sec. 19.

40.00 Set $\frac{1}{4}$ Sec. post, from which

A B. Oak, 12 ins. diam., bears N.51°W., 105 lks. dist.

A B. Oak, 12 ins. diam. bears S.55°E., 45 lks. dist.

45.00 Leave river valley, course S.70°W., and commence ascending a spur of mountains.

68.00 Top of spur. course S.20°E.

80.00 Set post Cor. of Secs. 19, 24, 25 and 30; from which

A Yellow Pine, 10 ins. diam., bears N.7°E., 475 lks. dist.

A Fir, 10 ins. diam., bears S.10°W., 250 lks. dist.

A B. Oak, 10 ins. diam., bears S.5°E., 815 lks. dist.

Impracticable to make trench.