

County Surveyor's Record, Douglas County, Oregon

Willamette Meridian, 2d Offset, T. 30 S., R. 4 W.

CHAINS 21.00	Foot of descent and begin to ascend on NW. slope of the mountain.
40.00	Set $\frac{1}{2}$ Sec. post, from which A Laurel, 18 ins. diam., bears N.40*E., 34 lks. dist. A Fir, 24 ins. diam. bears S.29*W., 77 lks. dist. Var. 18*50'E
41.00	Top of Western slope of ridge, C., E. and W., and commence gradual descent on SW. slope.
54.76	A Redwood, 24 ins. diam.
62.85	To a stream 4 lks. wide, course S.60*W., and commence ascent.
67.50	Summit of a ridge, C., E. and W., and commence steep descent on SW. slope of mountain.
80.00	Set a post, Cor. of Tps. 30 and 31 S., Rs. 4 and 5 W., from which A Fir, 14 ins. diam., bears N.34*E., 4 lks. dist., A Fir, 11 ins. diam., bears S.60*E., 17 lks. dist. A Laurel, 8 ins. diam., bears S.83*W., 33 lks. dist. A Live Oak, 7 ins. diam., bears N.50*W., 7 lks. dist.
	Land, rugged, rocky mountains.
	Soil, 2d rate, clay loam.
	Timber, Fir, Laurel, Maple, Redwood, etc.
	Undergrowth, Laurel, Hazel, Arrowwood, Live Oak, Manzanita, etc.
	South Bdy. of T. 30 S., R. 4 W., as surveyed by Nathaniel Ford, Deputy Surveyor, under Contract No. 44, dated May 30th, 1854.
	Var. 18 $\frac{1}{2}$ *W.
	West, on random line on the South Bdy. of Secs. 36, 35, 34, 33, 32 and 31, setting temporary mile and half mile posts.
478.20	Intersect West Bdy. 180 lks. North of Cor. of Tps. 29 and 30 South, on range line between 4 and 5 W. Therefore the correction will be N.89*47'E. on true Southern Bdy.