

County Surveyor's Record, Douglas County, Oregon

Subdivision of T. 30 S., R. 4 W.

CHAINS 40.14	Set $\frac{1}{4}$ Sec. post at average distance, from which A B. Oak, 8 ins. diam., bears S.83*W., 168 lks. dist. A B. Oak, 18 ins. diam., bears N.63*E., 228 lks. dist.	
80.28	To Sec. Cor. Third rate, high rolling land. Timber, Oak.	
40.00	North, between Secs. 13 and 14. Set $\frac{1}{4}$ Sec. post, from which A W. Oak, 7 ins. diam., bears S.60*W., 29 lks. dist. A B. Oak, 15 ins. diam., bears N.50*E., 13 lks. dist.	+75
80.00	Set post Cor. of Secs. 11, 12, 13 and 14, from which A Red Fir, 15 ins. diam., bears S.5*W., 55 lks. dist. A Red Fir, 5 ins. diam., bears S.85*E., 37 lks. dist. A Red Fir, 6 ins. diam., bears N.30*W., 35 lks. dist. A Red Fir, 18 ins. diam., bears N.3*E., 97 lks. dist. A white rock on head of South Myrtle Creek, course N.23*E. Soil, 3d rate, high rolling land. Scattering Oak.	+350
40.00	Var. 17*35'E. East, on random between Secs. 12 and 13. Set temp. $\frac{1}{4}$ Sec. post.	
80.36	Intersected East Bdy., 48 lks. N. of Sec. Cor. N.89*39'W. On true line between Secs. 12 and 13. Run on high ridge between Day's Creek and South Umpqua.	
40.18	Set $\frac{1}{4}$ Sec. post at average distance; from which A Red Fir, 18 ins. diam., bears N.82*W., 34 lks. dist. A Red Fir, 15 ins. diam., bears S.31*E., 130 lks. dist.	-25
48.00	Entered Oak openings.	-30
80.36	To Sec. Cor. Third rate land. Timber, Fir and Oak openings.	-50
	North, between Secs. 11 and 12.	