

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R. 4 W.

CHAINS		
3.50	Entered bottom, bears NW. and SE.	level
32.50	To left bank of S. Umpqua, course West. Chained across river.	-20
37.00	To right bank of river.	+25
40.00	Set $\frac{1}{4}$ Sec. post, from which A Pine, 48 ins. diam., bears N.70*W., 230 lks. dist. A Balm, 15 ins. diam., bears S.20*E., 250 lks. dist.	
80.00	Set post Cor. of Secs. 15, 16, 21 and 22, from which A B. Oak, 8 ins. diam., bears N.30*W., 122 lks. dist. A B. Oak, 6 ins. diam., bears N.7*E., 55 lks. dist. A B. Oak, 15 ins. diam., bears S.75*W., 90 lks. dist. A W. Oak, 5 ins. diam., bears S.30*E., 18 lks. dist. Soil, 2nd rate. Timber, Oak openings.	level
	Var. 17*45'E.	
	East, on random between Secs. 15 and 22.	
40.00	Set temp. $\frac{1}{4}$ Sec. post.	
80.52	Intersected E. bdy. 35 lks. N. of Sec. Cor. N.89*45'W. on true line between Secs. 15 and 22.	
40.26	Set $\frac{1}{4}$ Sec. post at average distance, from which A B. Oak, 10 ins. diam., bears N.42*E., 155 lks. dist. Made mound of stone.	-50
80.52	To Sec. Cor., 2nd rate land. Timber, Oak openings.	
	North, between Secs. 15 and 16.	
40.00	Set $\frac{1}{4}$ Sec. post, from which An Ash, 4 ins. diam., bears S.60*E., 30 lks. dist. A W. Oak, 6 ins. diam., bears S.45*W., 144 lks. dist.	level +30
42.50	Right bank of S. Umpqua, course N.37*E. Chained across river.	-20
47.75	Left bank of river.	