

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS

Timber, Oak openings.

This Township is principally composed of high hills, the Southern portion of heavily timbered mountains, Fir, Cedar, Laurel etc. South Umpqua River runs through it from SE. to NW. along the bottoms of which there is fine, rich land. Valley rather narrow.

Aug. 24, 1854.

Re-survey of Exterior lines of T. 30 S., R. 4 W., as surveyed by William Thiel, Deputy Surveyor, under Contract No. 535, dated Feb. 5th, 1889.

Offset Meridian through T. 30 S., Rgs. 4 and 5 W.

I begin at the Cor. of Tps. 29 and 30 S., Rs. 4 and 5 W., which, being gone, I restore by setting a Cedar post, 4½ ft. long, 4 ins. sq., 24 ins. in the ground, marked T 29 S S 31 on NE., R 4 W S 6 on SE., T 30 S S 1 on SW., R 5 W S 36 on NW. faces, with 6 notches on each edge, from which

A Redwood, 15 ins. diam., bears N.14\*W., 20 lks. dist. marked T 29 S R 5 W S 36 B T.

A Redwood, 15 ins. diam., bears S.75\*W., 35 lks. dist. marked T 30 S R 5 W S 1 B T.

A Redwood, 15 ins. diam., bears N.75\*E., 3 lks. dist., marked T 29 S R 4 W S 31 B T.

A Redwood, 15 ins. diam., bears S.65\*E., 67 lks. dist., marked T 30 S R 4 W S 6 B T.

In accordance with the field notes furnished me, all of which bearing trees I re-mark, as the old marks are overgrown and dim.

Thence I run

Var. 20\*30'E.

South, bet. Secs. 6 and 1.

Descend in Fir and Cedar timber.