

Re-survey of Exterior lines of T. 30 S., R. 4 W.
Offset Meridian through T. 30 S., Rs. 4 and 5 W.

CHAINS		
2.50	A branch, 3 lks. wide, course SW.; begin ascent.	
16.50	Top of spur, course NW.; begin slight descent.	
24.00	Top of 2nd spur, course NW.	
35.00	Leave Fir timber, top of ridge, course East.	
	Enter heavy underbrush; begin descent.	
40.05	<p>Intersect $\frac{1}{4}$ Sec. Cor. East 3 lks. dist., I restore this Cor. by setting a Laurel post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S on W. face, from which</p> <p>A Laurel, 14 ins. diam., bears N.37*E., 162 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A B. Oak, 9 ins. diam., bears N.20*W., 43 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>These are the old bearing trees, which I re-mark, as the old marks are dim and overgrown.</p>	-80
	Continue descending.	
42.50	Leave underbrush; enter prairie, bears E. and W.	
46.00	Leave prairie; enter Fir timber.	
52.80	Branch, 5 lks. wide, course S.30*E; begin ascent.	-150
78.60	Top of spur, bears E. and W.; descend slightly.	+500
80.20	<p>Intersect S. Bdy. of Sec. 6, 12 lks. E. of Cor. of Secs. 1, 6, 7 and 12. No post being found, I restore the corner by setting Black Oak post, 4$\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground, marked T 30 S S 6 on NE., R 4 W S 7 on SE., R 5 W S 12 on SW., S 1 on NW. faces, with 1 notch on N., and 5 notches on S. edges, from which</p> <p>A Laurel, 16 ins. diam., bears N.3*W., 150 lks. dist., marked T 30 S R 5 W S 1 B T.</p> <p>A B. Oak, 10 ins. diam., bears S.46*W., 57 lks. dist., marked T 30 S R 5 W S 12 B T.</p> <p>A B. Oak, 14 ins. diam., bears N.69*E., 60 lks. dist., marked T 30 S R 4 W S 6 B T.</p> <p>A Fir, 12 ins. diam., bears S.37*E., 50 lks. dist., marked T 30 S R 4 W S 7 B T.</p>	-20