

Resurvey of Exterior Lines, T. 30 S., R. 4 W.  
Offset Meridian through T. 30 S., Rs. 4 and 5 W.

CHAINS

R 5 W S 13 on SW., S 12 on the NW. faces, with 2 notches on N. and 4 notches on S. edges, from which

A B. Oak, 14 ins. diam., bears N.74\*E., 18 lks. dist., marked T 30 S R 4 W S 7 B T.

A W. Oak, 9 ins. diam., bears S.30\*E., 54 lks. dist., marked T 30 S R 4 W S 18 B T.

A B. Oak, 14 ins. diam., bears S.76½\*W., 14 lks. dist., marked T 30 S R 5 W S 13 B T.

A B. Oak, 13 ins. diam., bears N.37\*W., 70 lks. dist., marked T 30 S R 5 W S 12 B T.

Land, mountainous.

Soil, gravelly and 3rd rate.

Timber, Laurel, Oak and Pine.

Undergrowth, mostly young Laurel and Oak.

April 22, 1889.

Var. 16\*10'E.

South, bet. Secs. 18 and 13.

Steep descent of a rocky cliff.

16.00 Foot of cliff.

17.80 South Umpqua River, course S.60\*W. Set back flag, also set fore-flag on the S. bank, cross over, run base N.30\*30'E., 5.00 chains. Back flag bears N.34\*W., making 8.06 chs. across

25.86 S. bank of S. Umpqua, 18 ft. high.

26.00 County road to Canyonville, bears SW. and NE.

Var. 17\*20'E.

27.00 Enter field, level bottom; prairie.

40.00 Set a Cedar post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for ¼ Sec. Cor., marked ¼ S on W. face; impracticable to dig pits, as they would be injurious to the harvesting machines.

47.50 A small run, 3 lks. wide, course SW.