

County Surveyor's Record, Douglas County, Oregon

Resurvey of
South Boundary of T. 30 S., R. 4 W.

CHAINS		
	Keep descending through Fir timber along S. slope of mountain.	
18.50	A branch, course NW., 3 lks. wide; begin steep ascent of N. slope of spur.	-300
40.00	Set a Laurel post, 3 ft. long, 3 ins. sq., 24 ins. in ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which A Fir, 9 ins. diam., bears S.22*W., 18 lks. dist., marked $\frac{1}{4}$ S B T. A Fir, 10 ins. diam., bears N.2*W., 18 lks. dist., marked $\frac{1}{4}$ S B T.	+300
40.50	Top of spur, course N. and S.; begin steep descent of West slope. Var. 19*05'E.	+10
46.00	Pass to and descend NW. slope.	
50.00	A rocky cliff, 30 ft. high.	
61.50	A canyon, course NW., 60 ft. deep.	
70.60	Shively Creek, course N., 20 lks. wide.	-600
72.25	Leave bottom; ascend a steep SE. slope.	
80.00	Corner, a Fir, 6 ins. diam., for Cor. to Secs. 2, 3, 34 and 35, marked T 30 S S 35 on NE., R.4 W S 2 on SE., T 31 S S 3 on SW., S 34 on NW. faces, with 2 notches on E. and 4 notches on W. edges, from which A Maple, 6 ins. diam., bears N.25*E., 41 lks. dist., marked T 30 S R 4 W S 35 B T. A Fir, 36 ins. diam., bears S.17 $\frac{1}{2}$ *E., 97 lks. dist., marked T 31 S R 4 W S 2 B T. A Fir, 36 ins. diam., bears S.45 $\frac{1}{2}$ *W., 53 lks. dist., marked T 31 S R 4 W S 3 B T. A Fir, 8 ins. diam., bears N.67 $\frac{1}{2}$ *W., 14 lks. dist., marked T 30 S R 4 W S 34 B T.	+100
	Land, mountainous.	
	Soil, coarse gravel; 3rd rate.	