

## County Surveyor's Record, Douglas County, Oregon

Resurvey of  
South Boundary of T. 30 S., R. 4 W.

CHAINS		
25.00	A windfall of small Firs, bears N. and S. Var. 19°25'E.	
33.00	Top of spur, near its North end; begin descent.	+500
40.00	Set a Dogwood post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which A Maple, 6 ins. diam., bears N.18°W., 16 lks. dist., marked $\frac{1}{4}$ S B T. A Maple, 9 ins. diam., bears S.12°E., 27 lks. dist., marked $\frac{1}{4}$ S B T. Still descending.	-300
42.25	A canyon and branch, 3 lks. wide, course N.; begin ascent.	-80
51.50	Top of ascent on N. end of spur, course N. and S. Begin descent.	+200
56.20	A gulch, course N.; begin ascent.	-50
67.30	Head of canyon, course N.	+100
80.00	Set a Fir post, 4 $\frac{1}{2}$ ft. long, 4 ins. sq., 24 ins. in the ground, for Cor. to Secs. 32, 31, 5 and 6, marked T 30 S S 32 on NE., R 4 W S 5 on SE., T 31 S S 6 on SW., S 31 on NW. faces with 5 notches on E. and 1 notch on W. edges, from which A Fir, 27 ins. diam., bears N.31°E., 9 lks. dist., marked T 30 S R 4 W S 32 B T. A Fir, 10 ins. diam., bears S.13°E., 41 lks. dist., marked T 31 S R 4 W S 5 B T. A Fir, 24 ins. diam., bears S.63 $\frac{1}{2}$ °W., 22 lks. dist., marked T 31 S R 4 W S 6 B T. A Fir, 42 ins. diam., bears N.35°W., 62 lks. dist., marked T 30 S R 4 W S 31 B T. Land, mountainous. Soil, coarse gravel; 3rd rate. Timber, Fir, Cedar, Laurel and Maple.	+700