

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS

I replace the standing and partly decayed post by a W. Oak post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked T 30 S S 13 on NE., R 4 W S 24 on SE., S 23 on SW., S 14 on NW. faces, with 3 notches on S. and 1 notch on E. edges, from which

A B. Oak, 9 ins. diam., bears N.70*E., 19 lks. dist., marked T 30 S R 4 W B T. (Sec. omitted)

A B. Oak, 20 ins. diam., bears N.4*E., 41 lks. dist., marked T 30 S R 4 W S 13 B T.

A B. Oak, 16 ins. diam., bears S.75*E., 10 lks. dist., marked T 30 S R 4 W S 24 B T.

A B. Oak, 9 ins. diam., bears S.55*W., 19 lks. dist. marked T 30 S R 4 W S 23 B T.

A B. Oak, 10 ins. diam., bears N.61*W., 30 lks. dist., marked T 30 S R 4 W S 14 B T.

Thence

S.11'W., on true line bet. Secs. 23 and 24.

Var. 19*10'E.

Descend through Oak openings.

15.50 Bland's graves, East 40 lks.

21.00 Dry branch, course W.

22.60 Leave Oak openings; enter rolling prairie and Worley's enclosure.

28.75 A spring, in a dry gulch, bears E., 20 lks. dist.

39.80 $\frac{1}{4}$ Sec. Cor. post is gone; the bearing tree in Sec. 24 is standing; a stump of a B. Oak in Sec. 23, corresponding in size and direction with the description in the field notes. I restore this Cor., by setting a Fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, raise a mound of stone around it, marked $\frac{1}{4}$ S on the W. face, from which

A B. Oak, 33 ins. diam., bears S.55 $\frac{1}{2}$ *W., 115 lks. dist., marked $\frac{1}{4}$ S B T.