

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS		
	A Laurel, 3 ins. diam., bears S.24*E., 16 lks. dist., marked T 30 S R 3 W S 19 B T.	
	A Laurel, 4 ins. diam., bears S.18*W., 8 lks. dist., marked T 30 S R 4 W S 24 B T.	
	A Fir, 12 ins. diam., bears N.18*W., 35 lks. dist., marked T 30 S R 4 W S 13 B T.	
	Thence	
	S.55*40'W., on true line bet. Secs. 24 and 13.	
	Var. 18*50'E.	
	Ascend, through a thicket of young Oaks.	
6.90	Top of rise; descend slightly.	+50
9.00	A gully, course SE.; begin ascent.	-20
12.00	Leave thicket; enter Oak openings.	
14.00	Top of spur, course SE. and NW.; begin descent.	+30
20.80	A gully, course S.; begin ascent.	-70
23.50	Top of rise; begin descending.	+30
35.00	Foot of a cliff, 15 ft. high.	
40.00	A branch, course SE.; begin ascent.	-120
43.00	Top of rise on S. slope of hill; descend.	+50
45.15	A gully, course S.; ascend slightly.	-20
45.90	The Cor. to Secs. 13, 14, 23 and 24.	
	Land, hilly.	
	Soil, clay and fine gravel; 2nd rate.	
	Timber, Oaks and Laurels.	
	Undergrowth, mostly young Oaks and Laurels.	
	Var. 19*10'E.	
	North, on a random line bet. Secs. 13 and 14.	
39.60	1/4 Sec. Cor. bears E., 59 lks.	
77.50	Intersect North Bdy. of Sec. 14, 60 lks. West of Cor. to Secs. 11, 12, 13 and 14.	
	The post set for this Cor. is gone but all the bearing trees are standing, to-wit	