

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS		
	Var. 18*50'E.	
37.90	<p>$\frac{1}{4}$ Sec. Cor. post is gone, but both bearing trees, marked $\frac{1}{4}$ S B T are standing. I restore this Cor. by setting a W. Oak post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S on W. face, from which</p> <p>A W. Oak, 9 ins. diam., bears S.60*W., 29 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A B. Oak, 18 ins. diam., bears N.50*E., 13 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>These are the old bearing trees, which I re-mark as the old marks are dim.</p> <p>Thence</p> <p>S.51*W., on true line bet. Secs. 13 and 14.</p> <p style="text-align: right;">Var. 19*5'E.</p> <p>Descend through Oak openings.</p>	-400
5.00	Along the top of spur, course S.20*W. and N.20*E.	-60
15.50	Begin descent of E. hillside.	
28.00	Var. 18*50'E.	
32.00	A gully, course SE.	-250
39.60	<p>The Cor. of Secs. 13, 14, 23 and 24.</p> <p>Land, mountainous.</p> <p>Soil, rocky; 4th rate.</p> <p>Timber, Oak, Fir, Pine and Laurel.</p> <p style="text-align: right;">May 4, 1889.</p>	-50
	<p>East, on a random line Bet. Secs. 12 and 13.</p> <p style="text-align: right;">Var. 19*10'E.</p>	
39.06	<p>Intersect East Bdy. of T., 19.95 chs. S. of Cor. to Secs. 12, 13, 7 and 18, which is a basalt rock, 16x8x6, 12 ins. in the ground, marked with 2 notches on N. and 4 notches on S. edges, from which</p> <p>A Fir, 16 ins. diam., bears N.15*E., 17 lks. dist., marked T 30 S R 3 W S 7 B T.</p>	