

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS		
	<p>by setting a Fir post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, marked T 30 S S 1 on NE., R 4 W S 12 on SE., S 11 on SW., S 2 on NW. faces, with 5 notches on S. and 1 notch on E. edges, from which</p> <p>A W. Fir, 8 ins. diam., bears N.67*E., 20 lks. dist., marked T 30 S R 4 W S 1 B T.</p> <p>A Red Fir, 36 ins. diam., bears S.6*E., 51 lks. dist., marked T 30 S R 4 W S 12 B T.</p> <p>A Red Fir, 24 ins. diam., bears S.82*W., 52 lks. dist., marked T 30 S R 4 W S 11 B T.</p> <p>A Red Fir, 14 ins. diam., bears N.85*W., 20 lks. dist., marked T 30 S R 4 W S 2 B T.</p> <p>This is the old bearing tree, whose marks being dim, I re-mark same.</p>	
	<p>S.2*9'W., on true line bet. Secs. 11 and 12.</p> <p style="text-align: right;">Var. 18*50'E.</p>	
	<p>Ascend through Fir timber, heavy underbrush.</p>	
28.00	<p>Top of spur, course E. and W.; pass along W. slope of same.</p>	+300
39.00	<p>Canyon and branch, course NW., 2 lks. wide.</p>	-80
39.92	<p>Set a basalt rock, 15x10x6, 10 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ on W. face, from which</p> <p>A Fir, 18 ins. diam., bears N.69*W., 12 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A Fir, 16 ins. diam., bears S.57*E., 27 lks. dist., marked $\frac{1}{4}$ S B T.</p>	
	<p>Very steep ascent of NE. slope.</p> <p style="text-align: right;">Var. 19*30'E.</p>	
65.30	<p style="text-align: right;">Var. 19*10'E.</p>	
68.00	<p>Top of spur, course S.30*E. and N.30*W.; pass along NW. slope of spur.</p>	+600
70.50	<p>Leave Fir timber.</p>	
73.00	<p>A cliff, from which the whole valley is visible in the NW.</p>	