

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS 40.00	<p>Set a Cedar post, 4 ft. long, 4 ins. sq., 24 ins. in the ground, for Cor. to Secs. 22, 23, 26 and 27, marked T. 30 S S 23 on NE., R 4 W S 26 on SE., S 27 on SW., S 22 on NW. faces, with 2 notches on S. and E. edges, from which</p> <p>A Fir, 36 ins. diam., bears N.24*E., 26 lks. dist., marked T 30 S R 4 W S 23 B T.</p> <p>A Fir, 24 ins. diam., bears S.1*E., 102 lks. dist., marked T 30 S R 4 W S 26 B T.</p> <p>A Fir, 30 ins. diam., bears S.79*W., 44 lks. dist., marked T 30 S R 4 W S 27 B T.</p> <p>A Fir, 36 ins. diam., bears N.29*W., 76 lks. dist., marked T 30 S R 4 W S 22 B T.</p> <p>Thence</p> <p>East, on a random line bet. Secs. 23 and 26.</p> <p style="text-align: right;">Var. 18*35'E.</p> <p>Steep descent of E. slope through Fir timber.</p>	
40.00	Set temp. $\frac{1}{4}$ Sec. Cor.	
81.50	<p>Intersect N. and S. line, 75 lks. N. of Cor. to Secs. 23, 24, 25 and 26; then run</p> <p>N.89*28'W., on true line between Secs. 23 and 26.</p> <p style="text-align: right;">Var. 19*20'E.</p> <p>Low bottom, overflown in winter.</p>	
2.50	Higher bottom, covered with Fir timber.	
4.50	Foot of mountain; begin steep ascent of E. slope; Fir timber with dense underbrush.	
28.00	Ascent is less steep.	+800
40.00	Top of ridge, course S.70*W., and N.70*E.	+200
40.75	<p>Set a Maple post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for the $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which</p> <p>A Fir, 6 ins. diam., bears S.56$\frac{1}{2}$*W., 34 lks. dist., marked $\frac{1}{4}$ S B T.</p>	