

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 30 S., R. 4 W.

CHAINS

thence West 16.00 chs. to its SW. Cor., agreeing with the field notes of survey of said claim, thus verifying its original position. This is also the accepted Cor. by the settlers here.

I restore this Cor. by replacing the partially decayed post by a W. Oak post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, marked  $\frac{1}{4}$  S on W. face, from which  
 A B. Oak, 6 ins. diam., bears S.77\*E., 45 lks. dist., marked  $\frac{1}{4}$  S B T.  
 An Alder, 15 ins. diam., bears N.52\*W., 54 lks. dist., marked  $\frac{1}{4}$  S B T.

Thence

S.5\*52\*W., on true line bet. Secs. 10 and 11.

Var. 19\*10'E.

Through young Oaks and Firs; ascend.

9.00	A flat, densely covered by young Oaks.	+50
21.00	Canyon, course NW. and branch, 3 lks. wide. Begin steep ascent through Fir timber.	+60
34.00	Top of spur, course S.30*E. and N.30*W.; pass on NW. slope of same, still ascending.	+250
40.75	The Cor. of Secs. 10, 11, 14 and 15. Land, N. half, level and rolling; S. half, mountainous. Soil, N. half, good loam, 1st rate; S. half, gravelly, 3rd rate. Timber, Fir, Oak, Laurel, Ash, Maple and Alder. Undergrowth, young Fir, Oaks, Laurel, Hazel and Vine Maple. There is no trace of any survey on the South part of this line.	+80

Var. 18\*50'E.

East, on random line bet. Secs. 2 and 11.

40.00 Set temp.  $\frac{1}{4}$  Sec. Cor.