

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T 30 S., R. 4 W.

CHAINS	<p>A Fir, 12 ins. diam., bears N.88<math>\frac{1}{4}</math>*W., 67 lks. dist., marked T 30 S R 4 W S 21 B T.</p>	
	<p>Thence South, bet. Secs. 28 and 27. Var. 19*15'E.</p>	
	<p>Ascend through big Fir timber.</p>	
15.50	<p>Top of spur, course SE. and NW.; go along NW. slope of same.</p>	+150
17.00	<p>Enter heavy underbrush, ascending.</p>	+60
25.00	<p>Top of ascent; begin descent.</p>	
28.00	<p>A gulch, course W.; begin ascent.</p>	-40
30.50	<p>Top of rise; begin descent.</p>	+50
33.70	<p>A Gulch, course W.; begin steep ascent.</p>	-80
37.00	<p>Top of spur, C., NW. and SE.; begin descent.</p>	+160
40.00	<p>A Fir, 15 ins. diam., which I mark <math>\frac{1}{4}</math> S on W. face, for <math>\frac{1}{4}</math> Sec. Cor., from which A Fir, 36 ins. diam., bears N.60*W., 6 lks. dist., marked <math>\frac{1}{4}</math> S B T. A Fir, 27 ins. diam., bears N.71*E., 17 lks. dist., marked <math>\frac{1}{4}</math> S B T.</p>	-30
	<p>Land, mountainous. Soil, a coarse gravel; 3d rate. Timber, Fir, Cedar, Laurel and Maple. Undergrowth, Hazel, Chinquapin, young Firs and Laurel.</p>	
	<p>Var. 19*15'E.</p>	
	<p>East, on a random line bet. Secs. 22 and 27.</p>	
40.00	<p>Set temp. <math>\frac{1}{4}</math> Sec. Cor.</p>	
79.30	<p>Intersect N. and S. Line, 96 lks. N. of Cor. to Secs. 14, 15, 22 and 23.</p>	
	<p>Thence N.89*19'W., on true line between Secs. 22 and 27. Var. 18*35'E.</p>	
	<p>Through open Fir timber.</p>	
2.75	<p>Leave top of ridge, course S.30*E., and N. 30*W.; begin descending. Var. 19*15'E.</p>	
16.00	<p>A branch, course W., 2 lks. wide.</p>	