

Subdivisions of T. 30 S., R. 4 W.

CHAINS

resident of this locality, informs me that this is the original bearing tree. I restore this Cor. by setting a basalt stone, 20x8x8 ins., in a mound of stone, marked  $\frac{1}{4}$  on W. face, from which

A Maple, 30 ins. diam., bears S.20\*E., 260 lks. dist., marked  $\frac{1}{4}$  S B T.

A Balm, 24 ins. diam., bears S.33 $\frac{1}{2}$ \*W., 248 lks. dist., marked  $\frac{1}{4}$  S B T.

Thence

S.2\*W., on true line bet. Secs. 21 and 22.

Var. 18\*50'E.

5.35 Right bank of S. Umpqua River, course W. Set flag on left bank of river in line S.2\*W.; run base N.88\*W., 1.00 ch. Flag bears S.16\*25'E., making 389 lks. across.

9.24 Left bank of river, 15 ft. high; enter bottom covered with Fir timber and heavy underbrush.

13.00 Begin ascent.

20.00 Enter a timber flat, bears E. and W.

39.67 The Cor. to Secs. 21, 22, 28 and 27.

Land, hilly, except the middle portion, which is level. Soil, gravelly, 2nd rate except the middle 40 chs. which are good loam and 1st rate.

Timber, Fir, Oak, Laurel, Pine, Chinquapin, Maple, Alder and Balsam.

Undergrowth, Hazel, Vine Maple, young Firs, Oaks and Laurel.

Var. 19\*35'E.

East, on a random line bet. Secs. 15 and 22.

39.25  $\frac{1}{4}$  Sec. Cor. bears South 40 lks.

77.50 Intersect N. and S. line 40 lks. N. of Cor. to Secs. 14, 15, 22 and 23.

Thence

West, on true line bet. Secs. 15 and 22.

Var. 18\*35'E.

Ascend S. hillside, covered with Greasewood.

10.00 Geo. Worley's house bears S.55\*W.

Graham's house bears S.5 $\frac{1}{2}$ \*E.

+50