

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS 3.51	Left bank of the S. Umpqua river, course N.10*W. Enter small Pines, Fir and Oak.	
32.50	Enter low gravel bar.	
38.50	Left bank of S. Umpqua river, course NE., set flagg on right bank on line, thence, lay off base 90*, 1.50 chs. long. Flag shows angle 18*7' making 458 lks. across.	
43.08	Set a basalt stone 20x16x6 ins. in mound of stone, upon bed rock for witness corner to $\frac{1}{4}$ Sec. Cor. marked $\frac{1}{4}$ W C on W. face, 380 lks. S. of true Cor. in the river, from which A Pine. 24 ins. diam., bears W. 9 lks. dist., marked $\frac{1}{4}$ S W C B T. A B. Oak, 12 ins. diam., bears S.58 $\frac{1}{2}$ *E., 43 lks. dist marked $\frac{1}{4}$ S W C B T. The old corner and bearing trees are washed away.	
47.50	Leave timber bottom, begin ascent.	
60.50	County road to Canyonville, course N.30*E.	+50
61.50	Enter enclosure, begin slight ascent, through prairie, with scattering Oaks.	
76.50	Leave openings. Enter underbrush.	
78.57	The Cor. to Secs. 15, 16, 21 and 22. Land, rolling. Soil, gravelly, 2d rate. Timber, Oak, Fir, Pine, Laurel and Alder. Undergrowth, young Firs, Oaks and Laurels.	
	May 16, 1889.	
	Var. 19*5'E.	
	East, on random line between Secs. 10 and 15.	
39.28	$\frac{1}{4}$ Sec. Cor. bears S. 62 lks.	
77.48	Intersect N. and S. line 98 lks. North of Cor. to Secs. 11 10, 14 and 15. Thence N.89*28'W., on true line between Secs. 10 and 15.	
	Var. 19*30'E.	
	Bridge across S. Umpqua, bears N.75*W.	