

## County Surveyor's Record, Douglas County, Oregon

## Subdivision of T. 30 S., R. 4 W.

CHAINS  
47.00

Top of spur, course E. and W.; begin descent.

+60

54.94

Intersect N. Bdy. of Tp. 438 lks. W. of the  $\frac{1}{4}$  Sec. Cor. on S. Bdy. of Sec. 34, which is Yew post, 3 ins. Sq., firmly set in the ground, marked  $\frac{1}{4}$  S on N. face, from which

A Maple, 8 ins. diam., bears N.80\*E., 19 lks. dist., marked  $\frac{1}{4}$  S B T.

A Yew, 8 ins. diam., bears N.39\*E., 11 lks. dist., marked  $\frac{1}{4}$  S B T.

For closing Cor. of Secs. 3 and 4, I set a Fir post, 4 $\frac{1}{2}$  ft. long, 4 ins. sq., 24 ins. in the ground, marked C C T 30 S R 4 W on S. face, S 3 on E. face, S 4 on W. face, and 3 notches on E. and W. faces, from which

A Laurel, 16 ins. diam., bears S.65\*E., 34 lks. dist., marked T 30 S R 4 W S 3 B T.

A Fir, 36 ins. diam., bears S.8\*W., 24 lks. dist., marked T 30 S R 4 W S 4 B T.

Land, mountainous.

Soil, gravelly, 3d rate.

Timber, Fir, Cedar, Yew, Oak and Laurel.

Undergrowth, young Firs, Oaks, Laurel and Hazel.

May 18, 1889.

I return to Cor. of Secs. 20, 21, 28 and 29. Here I find three bearing trees, namely, a B. Oak, 25 ins. diam., marked S 20 B T., and a W. Oak, 22 ins. diam., marked S 21 B T., within 10 lks. of each other, E. and W., also a W. Oak 10 ins. diam., marked S 28 B T. But the distances given in the field notes are totally wrong. I also find the remains of a fence, built probably 25 years ago, running N. and S., also a later built fence, course E. and W. By taking the intersection of these fences, which were probably built when the original post stood, I find bearing tree N.2\*W. to stand 184 lks. instead of 18, bearing tree Sec. 28, 84 lks. dist., instead of 8 lks. This point is also verified