

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS	Secs. 9, 10, 15 and 16,	
	Thence	
	N.89*15'W., along true line between Secs. 16 and 9.	
	Var. 18*52'E.	
	From a point S. of Sec.. Cor. and on left bank of river	
	I run	
	N.31*W., 4.10 chs. to line, making a Westing of 211 lks.	
2.11	Left bank of S. Umpqua river, course N.20*W., enter high bank, covered by young Pines, Firs and Oaks. Level flat.	
13.00	Flook's house, bears S, 9*W.	
13.90	Enter enclosure, bears N. and S.	
21.50	Leave flat; begin ascent.	
23.00	Leave enclosure, heavy underbrush; go along N. slope of hill.	
31.50	Top of ascent; begin descent.	+60
40.12	Set a Fir post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ Sec. Cor., marked $\frac{1}{4}$ S on N. face, from which	
	A Fir, 12 ins. diam., bears N.51 $\frac{1}{2}$ *W., 31 lks. dist., marked $\frac{1}{4}$ S B T.	
	A B. Oak, 6 ins. diam., bears S.47*W., 8 lks. dist., marked $\frac{1}{4}$ S B T.	
	The old post set for this corner, and all the bearing trees have evidently been destroyed by fire about 25 years ago, as there are no trees growing here older than 25 years at the most.	
	Descend through heavy underbrush.	
42.00	A gulch, dry, course N.; begin ascent.	-50
46.00	Top of rise, along N. slope.	+50
67.00	Enter Oak openings; a flat bears N. and S.	
73.00	Foot of hill; enter bottom.	-30
76.00	Enter cornfield, bears N. and S.	
80.24	The Cor. to Secs. 8, 9, 16 and 17. Land, E. quarter level; W. three quarters hilly.	