

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 30 S., R. 4 W.

CHAINS	
	<p>A W. Oak, 28 ins. diam. bears S.7*W., 132 lks. dist., marked T 30 S R 4 W S 30 B T.</p> <p>A W. Oak, 14 ins. diam., bears N.56*W., 46 lks. dist., marked T 30 S R 4 W S 19 B T.</p> <p>These are the old bearing trees described in the field notes, which I remark, as the old marks are overgrown.</p> <p>Thence I run</p> <p>East, on a random line between Secs. 20 and 29.</p> <p style="text-align: right;">Var. 18*35'E.</p>
38.50	$\frac{1}{4}$ Sec. Cor. bears N. 58 lks.
77.87	Intersect N. and S. line, 11 lks, N. of corner, to Secs. 20, 21, 28 and 29,
	<p>Thence</p> <p>N.89*W., on true line between Secs. 20 and 29.</p> <p style="text-align: right;">Var. 19*5'E.</p> <p>Begin ascent along S. slope through prairie with scattering Oak.</p>
12.00	Top of spur, course N. and S; slight descent.
27.00	Prairie bears N.
28.00	A gulch, course S.; enter Oak timber, begin ascent. along S. slope of hill.
37.00	Top of ascent; begin descent.
39.37	<p>The $\frac{1}{4}$ Sec. Cor. The old post marked $\frac{1}{4}$ S is lying here, (the first found,) also both the bearing trees are standing. I restore this corner by setting a W. Oak post, 3 ft. long, 3 ins. sq., 24 ins. in the ground, marked $\frac{1}{4}$ S on the N. face, from which</p> <p>A B, Oak, 36 ins. diam., bears N.39*E., 48 lks., marked $\frac{1}{4}$ S B T.</p> <p>A W. Oak, 32 ins. diam., bears S.54*E., 64 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>Both are the old bearing trees, whose marks being overgrown, I renew.</p>