

Subdivisions of T 30 S., R 4 W.

CHAINS	
	<p>square, 24 ins. in the ground, marked T 30 S S 17 on NE., R 4 W S 20 on SE., S 19 on SW., S 18 on NW. faces, with 3 notches on S. and 5 notches on E. edges; from which</p> <p>A B. Oak, 12 ins. diam., bears N.33$\frac{1}{2}$*E., 65 lks. dist., marked T 30 S R 4 W S 17 B T.</p> <p>A laurel, 30 ins. diam., bears S.20-E., 34 lks. dist., marked T 30 S R 4 W S 20. B T.</p> <p>A fir, 16 ins. diam., bears S.5*W., 24 lks. dist., marked T 30 S R 4 W S 19 B T.</p> <p>A B. oak, 10 ins. diam., bears N.51$\frac{1}{2}$*W., 30 lks. dist., marked T 30 S R 4 W S 18 B T.</p> <p>These are all the original bearing trees corresponding to the description furnished me. I remark all of them, the old marks being overgrown.</p> <p>Thence</p> <p>S.35*W., on true line between Secs. 19 and 20.</p> <p style="text-align: right;">Var. 19*E.</p> <p>Ascend through heavy underbrush.</p>
6.00	Top of steep ascent, pass along NW slope of spur.
14.00	Top of rise on spur.
	<p>J. Weaver's house bears N.72$\frac{1}{2}$*W.</p> <p>Clough's barn bears N.35*W.</p> <p>Begin descent.</p>
27.50	A canyon, course NW., begin very steep ascent in fir timber.
39.05	<p>Top of spur, course NW and SE. $\frac{1}{4}$ Sec. Cor. The post of this corner is gone, but both the old bearing trees are standing. I restore this corner by setting a basalt stone 16x10x7 ins., marked $\frac{1}{4}$ on W. face, in a mound of stone, from which</p> <p>A B.Oak, 7 ins. diam., bears S.30*E., 25 lks. dist., marked $\frac{1}{4}$ S B T.</p> <p>A Laurel, 8 ins. diam., bears S.20*W., 43 lks. dist., marked $\frac{1}{4}$ S T B.</p>